

USB Gen1 Type-C 9-in-1 hub with HDMI™, VGA, 2x USB Gen1 Type-A, RJ45, SD/Micro SD card slots and USB Gen1 Type-C Female port



Product Name:

USB Gen1 Type-C 9-in-1 hub with HDMI™, VGA, 2x USB Gen1 Type-A, RJ45, SD/Micro SD card slots and USB Gen1 Type-C Female port

Product Series:

Docking

Product Code:

CSV-1594

EAN code:

8719214472177

UPC code:

841615102419

Description:

The Club 3D CSV-1594 USB Gen1 Type-C 9-in-1 hub with HDMI™, VGA, 2x USB Gen1 Type-A, RJ45, SD/Micro SD card slots and USB Gen1 Type-C Female port, provides a very advanced, efficient solution to extend a single USB Gen1 Type-C port to be multiple ports. It integrates video, data and power ports that allows to connect 2 displays simultaneously for enjoying videos on a larger screen, connect multiple USB Gen1 devices for data transmission up to 5Gbps, connect a Gigabit Ethernet source for getting your PC connected to super high speed network, or connect to headset to enjoy fantastic music. It also provides PD charging for support up to max. 100W PD charging. This is for operating this device and charge the host simultaneously. It can work on all DP™1.2 Alt mode supported USB Gen1 Type-C hosts.

Features:

- Support DP™1.2 Alt mode
 - Support HDMI™ max 4K@30Hz
 - Support HDCP1.4
 - Support VGA max 1080P@60Hz output
 - Support to output 2 video under SST mode with dual 1080P@60Hz
 - Max 5Gbps data transmission per USB Gen1 Type-A port
 - Support max 7.5W(5V/1.5A) downstream charging, 2 USB Gen1 Type-A share max 1.8A output
 - Support Gigabit Ethernet 10M/100M/1000M, RJ45 support to work with Nintendo Switch™ *
 - Support SD3.0 UHS-I up to 104MBps data rate, allow 2 card slots to work simultaneously
 - Support Phone out and Mic in
 - Support voice adjustment function when connected to headset
 - Support PD3.0 with max 100W PD charging
- *Note Only RJ45 port provides support for the Nintendo Switch™, other ports don't support the Nintendo Switch™ !

Input:

- 1x USB Gen1 Type-C Male (Connect to host)

Note: To get max bandwidth, the host should support DP™1.2 Alt mode

Output(s):

- 1x HDMI™
 - Support max 4K@30Hz
 - Support 8/10 bit color depth output
 - Support output pixel format RGB/YCbCr4:4:4/YCbCr4:2:2
 - Support HDCP1.4
- 1x VGA
 - Support max 1080P@60Hz output
 - Support to output 2 video under SST mode with dual 1080P@60Hz
- Note: The max resolution of the display determined by the computer and the monitor
- 2x USB Gen1 Type-A
 - Max 5Gbps data transmission per port
 - Support max 7.5W(5V/1.5A) downstream charging the other port supports max. 900mA downstream charging.
- 2 USB Gen1 Type-A ports share max 1.8A output
 - Support short-circuit, over-current, over-voltage protection
- 1x RJ45
 - Support Gigabit Ethernet 10M/100M/1000M
 - Support Wake-On-LAN
 - Support full duplex flow control
 - Support to work with Nintendo Switch™
 - Light indicator indicates the state, no light when no Internet connected, orange light turns on when network connection is established, green light flashes when transmitting data
- 2x SD/Micro SD 3.0
 - Support SD3.0 UHS-I up to 104MBps data rate
 - Allow 2 card slots to work simultaneously
- 1x 3.5mm Audio jack
 - Support Phone out with digital audio max 96KHz/24bit sampling rate
 - Support Mic in with digital audio max 96KHz/24bit sampling rate
 - DAC SNR MAX 95 dB
 - Support CTIA/GMTP auto detection
 - Support voice adjustment function when connected to headset
- 1x USB Gen1 Type-C Female (for PD Charging)
 - Support max 100W PD charging
 - Support PD3.0 Fast Role Swap, the connected device will not get disconnected while plugging in and out the PD Adapter
 - 15W is dedicated to the functioning of this product, the rest power (max 85W) will be passed to charge for the host

Note:

- Please update your TV Firmware to the version which supports these resolutions/refresh rates !
- Please update your Graphic drivers on your PC and make sure that DSC1.2 is supported on your devices to support the these resolutions/refresh rates!

Please use one of our Extension/Adapter cables to connect to your devices: In case you need assistance to choose the correct cable, please visit our website www.club-3d.com or feel free to mail us at support@club-3d.com and it will be our pleasure to assist you.



NOTE: Please make sure your host supports DP™1.2 Alt mode.

OS Support:

- All

In the box:

- 1x USB Gen1 Type-C 9-in-1 hub with HDMI™, VGA, 2x USB Gen1 Type-A, RJ45, SD/Micro SD card slots and USB Gen1 Type-C Female port
- 1x Quick Install Guide(QIG)

Available Interfaces

Input:

- USB Gen1 Type-C Male (Connect to host)

Output:

- 1x HDMI™ Female
- 1x VGA Female
- 2x USB Gen1 Type-A Female
- 1x RJ45
- 1x SD/Micro SD 3.0
- 1x 3.5mm jack Audio
- 1x USB Gen1 Type-C Female

Other info:

- Box size: 7 x 32 x 3.5cm / 2.76 x 12.6 x 1.38"
- Cable length approx.: 15 cm / 5.90"
- Total length: ± 31.6 cm / 12.44"
- Hub dimensions: 12.5 x 5.9 x 1.4 cm / 4.92 x 2.32 x 0.55"
- Connector dimensions: 3.4 x 1.2 x 0.65 cm / 0.86 x 0.47 x 0.26"
- Product Weight: 117 gr / 4.13 oz
- Box Weight: 42 gr / 1.48 oz
- LDPE Bag Weight: 6 gr / 0.21 oz
- Total Weight: 165 gr / 5.82 oz
- Meets ROHS, FCC, and CE EMI requirements

Input:

