

# USB Gen1 Type-C 7-in-1 hub with 2x HDMI™, 2x USB Gen1 Type-A, 1x RJ45, 1x 3.5mm Audio, 1x USB Gen1 Type-C 100W Female port



## Product Name:

USB Gen1 Type-C 7-in-1 hub with 2x HDMI™, 2x USB Gen1 Type-A, 1x RJ45, 1x 3.5mm Audio, 1x USB Gen1 Type-C 100W Female port

## Product Series:

Docking

## Product Code:

CSV-1595

## EAN code:

8719214472269

## UPC code:

841615102501

## Description:

The Club 3D CSV-1595 USB Gen1 Type-C 7-in-1 hub with 2x HDMI™, 2x USB Gen1 Type-A, 1x RJ45, 1x 3.5mm Audio, 1x USB Gen1 Type-C 100W Female port, provides a very advanced, efficient solution to extend a single USB Gen1 Type-C port to multiple ports. It integrates video, data and power ports that allows to connect 2 displays simultaneously for enjoying videos on a larger screen, connect multiple USB Gen1 devices for data transmission up to 5Gbps, connect a Gigabit Ethernet source for getting your PC connected to super high speed network, or connect to headset to enjoy fantastic music. It also provides PD charging for support up to max. 100W PD charging. This is for operating this device and charge the host simultaneously. It can work on all DP™1.4 Alt mode supported USB Gen1 Type-C hosts.

## Features:

- Support DP™1.4 Alt mode
- Support HDMI™ max 4K@60Hz from the USB Type-C Display Alternate Mode function
- Support HDMI™ max 4K@30Hz from the integrated chipset in the dock - make sure to install the driver from our website at [www.club-3d.com](http://www.club-3d.com)
- Support HDCP1.4, HDCP 2.2 ( on the HDMI with AltMode Function only)
- Support dual displays for Mac M1 / M2 users.\*
- Max 5Gbps data transmission per USB Gen1 Type-A port
- Support max 7.5W(5V/1.5A) downstream charging, 2 USB Gen1 Type-A BC1.2
- Support Gigabit Ethernet 10M/100M/1000M, RJ45
- Support Audio output
- Support 1x USB Type C Female PD3.0 with max 100W PD charging and Gen1 5Gbps of data transfer

## NOTE:

Please make sure your host supports DP™1.4 Alt mode

**\* For Mac OSX users please download driver from the CSV-1595 product page at our website.**

## OS Support:

- All

## In the box:

- 1x USB Gen1 Type-C 7-in-1 hub with 2x HDMI™, 2x USB Gen1 Type-A, 1x RJ45, 1x 3.5mm Audio, 1x USB Gen1 Type-C 100W Female port
- 1x Quick Install Guide(QIG)

## Note:

- Please update your TV Firmware to the version which supports these resolutions/refresh rates !
- Please update your Graphic drivers on your PC and make sure that DSC1.2 is supported on your devices to support the these resolutions/refresh rates!

Please use one of our Extension/Adapter cables to connect to your devices. In case you need assistance to choose the correct cable, please visit our website [www.club-3d.com](http://www.club-3d.com) or feel free to mail us at [support@club-3d.com](mailto:support@club-3d.com) and it will be our pleasure to assist you.

**Disclaimer:** While we endeavour to provide the most accurate, up-to-date information available, the content on this document may be out of date or include omissions, inaccuracies or other errors. Therefore Club 3D does not accept any rights claimed on the content of this document. Please refer to a full overview of our Legacy Terms and Conditions on [www.club-3d.com](http://www.club-3d.com). All other brand names are trademarks or registered trademarks and are the property of their respective owners. All content is subject to change without prior notice.



## Available Interfaces

### Input:

- USB Gen1 Type-C Male (Connect to host)  
Support DP™1.4 Alt mode

**Note:** To get max bandwidth, the host should support DP™1.4 Alt mode

### Output:

- Single and Dual displays
  - 1x HDMI™  
Support max 4K@30Hz  
Support 8/10 bit color depth output  
Support output pixel format RGB/YCbCr4:4:4/YCbCr4:2:2
  - 1x HDMI™ Alt Mode  
Support max 4K@60Hz  
Support 8/10 bit color depth output  
Support output pixel format RGB/YCbCr4:4:4/YCbCr4:2:2  
Support HDCP 2.2
  - 2x USB Gen1 Type-A  
Max 5Gbps data transmission per port  
Support max 7.5W(5V/1.5A) downstream charging  
Support short-circuit, over-current, over-voltage protection
- 1x RJ45  
Support Gigabit Ethernet, 10M/100M/1000M  
Light indicator indicates the state, no light when no Internet connected, orange light turns on when network connection is established, green light flashes when transmitting data
- 1x 3.5mm Audio jack  
Support Mic in with digital audio max 48K/16bit sampling rate
- 1x USB Gen1 Type-C Female (for PD Charging)  
Support max 100W PD charging  
Support PD3.0 Fast Role Swap  
Support Gen 1 - 5Gbps of data transfer

## Other info:

- Box size: 21 x 21 x 3.5 cm / 8.27 x 8.27 x 1.38"
- Cable length: ± 25 cm / ± 9.84"
- Total length: ± 39 cm / 15.35"
- Hub dimensions: 14 x 6.5 x 1.9 cm / 5.51 x 2.56 x 0.75"
- Product Weight: 210 gr / 7.41 oz
- Box Weight: 70 gr / 2.47 oz
- LDPE Bag Weight: 6 gr / 0.21 oz
- Total Weight: 286 gr / 10.09 oz
- Meets ROHS, FCC, and CE EMI requirements

### Input:



### Output:

